

95%-96% GAS FURNACES

ASSEMBLED IN TRENTON, NEW JERSEY



- ▶ 34" cabinet height on all models
- ▶ Up to 96% AFUE
- ▶ 2 - 5 ton models available in each family
- ▶ Stainless steel primary and secondary heat exchangers
- ▶ Compliant with California 40ng/J Low-NOx requirements



Model Number	Input BTU/h	Nominal Airflow (Tons)	Dimensions (Inches) H x W x D	Motor Type	Application	AFUE
--------------	-------------	------------------------	-------------------------------	------------	-------------	------

A951X Constant Torque 95-96% AFUE

A951X040BU3SAB	40,000	2-3	34 x 17.5 x 28.75	Constant Torque (ECM)	Upflow	96%
A951X060BU4SAB	60,000	3-4	34 x 17.5 x 28.75			96%
A951X080BU4SAB	80,000	3-4	34 x 17.5 x 28.75			96%
A951X080CU5SAB	80,000	4-5	34 x 21 x 28.75			96%
A951X100CU5SAB	100,000	4-5	34 x 21 x 28.75			95%
A951X120DU5SAB	120,000	5	34 x 24.5 x 28.75			95%

A951X040BD3SAB	40,000	2-3	34 x 17.5 x 28.75	Constant Torque (ECM)	Downflow	96%
A951X060BD3SAB	60,000	3	34 x 17.5 x 28.75			96%
A951X080BD4SAB	80,000	4	34 x 17.5 x 28.75			95%
A951X100CD5SAB	100,000	5	34 x 21 x 28.75			96%
A951X120DD5SAB	120,000	5	34 x 24.5 x 28.75			95%

A952V Variable Speed 96% AFUE

A952V040BU3SBA	40,000	3	34 x 17.5 x 28.75	Var Speed ECM	Upflow	96%
A952V060BU3SAD	60,000	3	34 x 17.5 x 28.75			96%
A952V060BU4SBA	60,000	4	34 x 17.5 x 28.75			96%
A952V080BU4SBA	80,000	4	34 x 17.5 x 28.75			96%
A952V080CU5SBA	80,000	5	34 x 21 x 28.75			96%
A952V100CU4SAD	100,000	4	34 x 21 x 28.75			96%
A952V100CU5SBA	100,000	5	34 x 21 x 28.75			96%
A952V120DU5SBA	120,000	5	34 x 24.5 x 28.75			96%

A952V040BD3SBA	40,000	3	34 x 17.5 x 28.75	Var Speed ECM	Downflow	96%
A952V060BD3SBA	60,000	3	34 x 17.5 x 28.75			96%
A952V080BD4SBA	80,000	4	34 x 17.5 x 28.75			96%
A952V100CD4SAD	100,000	4	34 x 21 x 28.75			96%
A952V100CD5SBA	100,000	5	34 x 21 x 28.75			96%
A952V120DD5SBA	120,000	5	34 x 24.5 x 28.75			96%

5 YEAR WARRANTY

Limited functional parts warranty

10 YEAR WARRANTY

Functional parts warranty with product registration